

Model : ES18x09 18W
V1 : +9V / 2.0A

AC-DC Single Output adaptor

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	80mVp-p (Typ)	I/P:230VAC O/P:FULL LOAD Ta:25°C	8mVp-p	P
2	VOLTAGE TOLERANCE	-5% - +5% (Max)	I/P:90VAC~264VAC O/P:FULL-MIN. LOAD Ta:25°C	-1.57% ~ +1.60%	P
3	LINE REGULATION	-1% - +1% (Max)	I/P:90VAC ~264VAC O/P:FULL LOAD Ta:25°C	-0% ~ +0%	P
4	LOAD REGULATION	-5% - +5% (Max)	I/P:230VAC O/P:FULL ~MIN LOAD Ta:25°C	-1.57% ~ +1.60%	P
5	SET UP TIME	300 mS (Max)	I/P:230VAC O/P:FULL LOAD Ta:25°C	21.96 mS	P
6	RISE TIME	100 mS (Max)	I/P:230VAC O/P:FULL LOAD Ta:25°C	12.5 mS	P
7	HOLD UP TIME	16 mS (Min)	I/P:115VAC O/P:FULL LOAD Ta:25°C	45.2 mS	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE RANGE	100VAC ~ 240VAC (Typ)	I/P:TESTING O/P:FULL LOAD Ta:25°C	70V ~ 264V	P
2	FREQUENCY RANGE	50HZ - 60HZ (Typ) NO DAMAGE OSC	I/P: 100VAC ~ 240VAC O/P:FULL-MIN LOAD Ta:25°C	TEST: OK	P
3	EFFICIENCY	72% (Typ)	I/P:230VAC O/P:FULL LOAD Ta:25°C	76.2%	P
4	AC CURRENT	0.5A (Max)	I/P: 100VAC O/P:FULL LOAD Ta:25°C	0.38A	P
5	INRUSH CURRENT	< 40A COLD START	I/P:230VAC O/P:FULL LOAD Ta:25°C	24.0A	P
6	LEAKAGE CURRENT	< 0.75mA FOR CLASS I < 0.25mA FOR CLASS II	I/P:240VAC O/P:Min LOAD Ta:25°C	L-FG:0.02mA N-FG:0.02mA	P

4	RADIATION	EN55022 CLASS B	I/P:230VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS	P
5	E.S.D	IEC61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	E.F.T	IEC61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N :1KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
8	WITHSTAND VOLTAGE	I/P-O/P:3KVAC/min	I/P-O/P:3KVAC/min Ta:25°C	I/P-O/P:1.757 mA NO DAMAGE	P
9	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500VDC Ta:25°C	I/P-O/P:>100MΩ NO DAMAGE	P

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SUPPOSE C301 IS THE MOST CRITICAL COMPONENT	I/P:230 VAC O/P:FULL LOAD Ta=25°C LIFE TIME=151687HRS I/P:230 VAC O/P:FULL LOAD Ta=40°C LIFE TIME=59094HRS I/P:230 VAC O/P:70% LOAD Ta=50°C LIFE TIME=70764HRS I/P:115 VAC O/P:FULL LOAD Ta=25°C LIFE TIME=128441HRS		P
2	MTBF	MIL-HDBK-217F NOTICES2 STRESS ANALYSIS PREDICTION TOTAL FAILURE RATE: 1.580515 M.T.B.F: 632705HRS			P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2007.12.25	STOCK	PASS	PETER	T.K.CHENG