

MODEL : NES-15-48

## OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 240 mVp-p (Max)	I/P: 230VAC O/P:FULL LOAD Ta:25°C	V1: 36 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1: 43.2V - 52.8 V	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	42.29 V- 57.04 V/ 230 VAC 42.29 V- 57.04 V/ 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1: 1 % - -1 % (Max)	I/P:85 VAC / 264 VAC O/P:FULL/ MIN LOAD Ta:25°C	V1: 0.02 %- -0.02 %	P
4	LINE REGULATION	V1: 0.5 %- -0.5 % (Max)	I/P: 85 VAC ~ 264 VAC O/P:FULL LOAD Ta:25°C	V1: 0 %- 0 %	P
5	LOAD REGULATION	V1: 0.5 %- -0.5 % (Max)	I/P: 230 VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: 0.02 %- -0.02 %	P
6	SET UP TIME	230VAC: 1000 ms (Max) 115 VAC: 1000 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 730 ms 115VAC/ 730 ms	P
7	RISE TIME	230VAC: 30 ms (Max) 115VAC: 30 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 9 ms 115VAC/ 10 ms	P
8	HOLD UP TIME	230VAC: 100 ms (TYP) 115VAC: 20 ms (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 105 ms 115VAC/ 22 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: <5 %	P
10	DYNAMIC LOAD	V1: 4800 mVp-p	I/P: 230 VAC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	267 mVp-p	P

## INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	85VAC~264 VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	78 V~264V	P
			I/P: LOW-LINE-3V= 82V HIGH-LINE+15%=300 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN ( AC POWER ON/OFF NO DAMAGE )	TEST: OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P: 85VAC ~ 264 VAC O/P:FULL~MIN LOAD Ta:25°C	TEST: OK	P
3	EFFICIENCY	82 % (TYP)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	82.2 %	P
4	INPUT CURRENT	230V/ 0.25 A (TYP) 115V/ 0.45 A (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	I = 0.18 A/ 230 VAC I = 0.3 A/ 115 VAC	P
5	INRUSH CURRENT	230V/ 45 A (TYP) COLD START	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	I = 34 A/ 230 VAC	P
6	LEAKAGE CURRENT	< 2 mA / 240 VAC	I/P: 254 VAC O/P:Min LOAD Ta:25°C	L-FG: 0.1 mA N-FG: 0.1 mA	P

## PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	Above 105% rated output power	I/P: 230 VAC I/P: 115 VAC O/P:TESTING Ta:25°C	200 %/ 230 VAC 131%/ 115 VAC Hiccup Model	P
2	OVER VOLTAGE PROTECTION	CH1: 55.2V~ 64.8 V	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	60 V/ 230 VAC 60 V/ 115 VAC Shut off	P
3	OVER TEMPERATURE PROTECTION	U1 Tj 140°C typically (U1)Detect on main control IC	I/P: 230VAC O/P:FULL LOAD	O.T.P. Active Shut down o/p volotage , recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P:FULL LOAD Ta:25°C	NO DAMAGE Constant Current Limiting	P

## ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT																																																							
1	TEMPERATURE RISE TEST	MODEL : NES-15-24 1. ROOM AMBIENT BURN-IN : 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 26.3 °C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 51.2 °C																																																										
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 26.3 °C</th> <th>HIGH AMBIENT Ta= 26.3 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>LF-507</td><td>47.4°C</td><td>71.5°C</td></tr> <tr><td>2</td><td>BD1</td><td>KBJ208G 2A/800V LT</td><td>47.2°C</td><td>70.7°C</td></tr> <tr><td>3</td><td>C5</td><td>47U/400V CAPX 105°C</td><td>46.9°C</td><td>70.3°C</td></tr> <tr><td>4</td><td>ZD1</td><td>P6KE200</td><td>51.2°C</td><td>74.9°C</td></tr> <tr><td>5</td><td>D1</td><td>BYV26C 1A/600V</td><td>56.8°C</td><td>80.7°C</td></tr> <tr><td>6</td><td>C36</td><td>47U/50V NCC 105°C KY</td><td>48.3°C</td><td>73.1°C</td></tr> <tr><td>7</td><td>U1</td><td>FSDM0265</td><td>61.2°C</td><td>86.0°C</td></tr> <tr><td>8</td><td>T1 COIL</td><td>TF-1234</td><td>59.4°C</td><td>80.9°C</td></tr> <tr><td>9</td><td>D100</td><td>BYQ28X-200 10A/200V PH</td><td>65.6°C</td><td>86.0°C</td></tr> <tr><td>10</td><td>C105</td><td>330U/35V CAPX 105°C GL</td><td>49.5°C</td><td>72.0°C</td></tr> </tbody> </table>	NO	Position	P/N	ROOM AMBIENT Ta= 26.3 °C	HIGH AMBIENT Ta= 26.3 °C	1	LF1	LF-507	47.4°C	71.5°C	2	BD1	KBJ208G 2A/800V LT	47.2°C	70.7°C	3	C5	47U/400V CAPX 105°C	46.9°C	70.3°C	4	ZD1	P6KE200	51.2°C	74.9°C	5	D1	BYV26C 1A/600V	56.8°C	80.7°C	6	C36	47U/50V NCC 105°C KY	48.3°C	73.1°C	7	U1	FSDM0265	61.2°C	86.0°C	8	T1 COIL	TF-1234	59.4°C	80.9°C	9	D100	BYQ28X-200 10A/200V PH	65.6°C	86.0°C	10	C105	330U/35V CAPX 105°C GL	49.5°C	72.0°C			P
NO	Position	P/N	ROOM AMBIENT Ta= 26.3 °C	HIGH AMBIENT Ta= 26.3 °C																																																								
1	LF1	LF-507	47.4°C	71.5°C																																																								
2	BD1	KBJ208G 2A/800V LT	47.2°C	70.7°C																																																								
3	C5	47U/400V CAPX 105°C	46.9°C	70.3°C																																																								
4	ZD1	P6KE200	51.2°C	74.9°C																																																								
5	D1	BYV26C 1A/600V	56.8°C	80.7°C																																																								
6	C36	47U/50V NCC 105°C KY	48.3°C	73.1°C																																																								
7	U1	FSDM0265	61.2°C	86.0°C																																																								
8	T1 COIL	TF-1234	59.4°C	80.9°C																																																								
9	D100	BYQ28X-200 10A/200V PH	65.6°C	86.0°C																																																								
10	C105	330U/35V CAPX 105°C GL	49.5°C	72.0°C																																																								
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR ( MIN )	I/P: 230 VAC O/P: 132 % LOAD Ta:25°C	TEST : OK	P																																																							
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 230 VAC O/P: 100 % LOAD Ta= -20°C	TEST : OK	P																																																							
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P: 272 VAC O/P:FULL LOAD Ta= 50°C HUMIDITY= 95 %R.H	TEST : OK	P																																																							
5	TEMPERATURE COEFFICIENT	± 0.03 %(0~45°C)	I/P: 230 VAC O/P:FULL LOAD	± 0.01%(0~50°C)	P																																																							
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10~500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	P																																																							

### SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3 KVAC/min I/P-FG: 1.5 KVAC/min O/P-FG: 0.5 KVAC/min	I/P-O/P: 3.6 KVAC/min I/P-FG: 1.8 KVAC/min O/P-FG: 0.6 KVAC/min Ta:25°C	I/P-O/P: 1.05 mA I/P-FG: 0.78 mA O/P-FG: 0.72 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 13 GΩ I/P-FG: 12 GΩ O/P-FG: 30 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta:25°C	3 mΩ	P
4	APPROVAL	TUV: Certificate NO : UL: File NO : E183223			P

### E.M.C TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N :1KV L,N-PE:2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

### M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SUPPOSE C105 IS THE MOST CRITICAL COMPONENT I/P: 230VAC O/P:FULL LOAD Ta= 25 °C LIFE TIME= 300185 HRS I/P: 230VAC O/P:FULL LOAD Ta= 50 °C LIFE TIME= 62648 HRS			P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE:563.5K HRS			P



COMPONENT STRESS TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor ( D to S) or (C to E) <b>Peak Voltage</b>	U1 Rated FSDH0265 : 650V 50uA	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) 502 V (2) 484 V (3) 582 V	P
2	Diode Peak <b>Voltage</b>	D101 Rated HER306 : 600V 3A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) 289 V (2) 331 V (3) 287 V	P
3	Clamp Diode Peak <b>Voltage</b>	D1 Rated BYV26C : 600 V 1A	I/P:High-Line +3V = 267 V O/P: (1)Full Load (2) Dynamic Load 90%Duty/1KHz Ta:25°C	(1) 446 V (2) 464 V	P
4	<b>Input Capacitor Voltage</b>	C5 Rated : 47u /400V/ 105°C	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change (4)Burn in 1hour Ta:25°C	(1) 384 V (2) 384 V (3) 388 V (4) 388 V	P
5	<b>Control IC Voltage Test</b>	U1 Rated FSDH0265 : 20V	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 16.7 V (2) 12.7 V (3) 13.5 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2005/5/6	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2005/6/28	PRODUCT SAMPLE W0505B05	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023